

COMPARISON CHART

PANOPTIX



PS21-TM
Forward View



PS22-TR
Forward & Down View



PS30
Down View



PS31
Forward View



PS51-TH
Forward View



PS60
Down View



LiveScope™ LVS12
Forward & Down View



LiveScope™ LVS32
Forward & Down View

PANOPTIX LIVESCOPE™ DOWN							•	•
PANOPTIX LIVESCOPE™ FORWARD							•	•
PANOPTIX LIVESCOPE™ PERSPECTIVE MODE								• Only with Perspective Mode Mount
LIVEVÜ FORWARD	•	•		•	•			
REALVÜ 3D FORWARD				•				
FRONTVÜ	•			•	•			
LIVEVÜ DOWN		•	•			•		
REALVÜ 3D HISTORICAL DOWN			•			•		
REALVÜ 3D DOWN			•			•		
FREQUENCY (KHz)	417 kHz	417 kHz	417 kHz	417 kHz	417 kHz	417 kHz	530 - 1,100 kHz	530 - 1,100 kHz
POWER	48 W	48 W	144 W	144 W	144 W	144 W	500 W	500 W
BEAM WIDTH	90° x 20°	90° x 20°	LiveVü Down: 120°/10°, 120°/20°, 120°/40° (+/- 45° fore/aft) RealVü Hist.: 120°x6° RealVü Down: 90°x120° (+/- 45° fore/aft sweep)	LiveVü Forward: 10°x90°, 20°x90°, 40°x90° (+/- 30° port/stbd) RealVü 3D Forward: 60°x90° (+/- 30° port/stbd sweep)	90° x 20°	LiveVü Down: 120°/10°, 120°/20°, 120°/40° (+/- 45° fore/aft) RealVü Hist.: 120°x6° RealVü Down: 90°x120° (+/- 45° fore/aft sweep)	30° x 20° Forward 30° x 20° Down	20° x 135° Forward 20° x 135° Down
MAXIMUM DEPTH	300 ft.	300 ft. Down 100 ft. Forward	300 ft.	300 ft.	300 ft.	300 ft.	Down & Forward: 200 ft.	Down & Forward: 200 ft.
DEPTH / SPEED / TEMPERATURE	Depth & Temp	Depth & Temp	Depth	Depth	Depth & Temp	Depth & Temp	Depth	Depth
TRANSOM MOUNT INCLUDED	•		•	•			•	•
TROLLING MOTOR MOUNT INCLUDED		•		•			•	•
THRU-HULL MOUNT INCLUDED					•	•		• Only with Panoptix LiveScope Thru-Hull, 010-02233-00